

POS 5000



With the smallest distributed footprint in the Flytech POS PC series, the Flytech POS 5000 delivers a tremendous amount of power in a compact design for an extremely solid image. This POS 5000 system can be configured as a thick-client, stand-alone solution or centrally controlled workstation.

- Unique features such as, HDD toolfree service, modular service design.
- Flexibility, upgradability and interchangeability are the key design concepts of the POS PC.



Features



1. Small in size but consolidated in design



4. Tool free HDD and ODD access with RAID 0,1 built-in



2. Modular design for easy maintenance



5. Optional powered USB ports



3. Rich I / O connector ports



6. Optional internal ODD

POS 5000



Specification

Model Name	POS 5000
Motherboard	B99
CPU	Intel P4 / Celeron / Core 2 Duo Processor LGA775
Chipset	Intel 945G FSB 533 / 800 / 1066 MHZ / ICH7R
System Memory	2 x DDR2 DIMM Slots Up to 4GB
Graphic Memory	System Memory Shared Up to 232MB
Storage	
HDD	2 x 3.5" SATA HDD available
ODD	1 x Slim CD-ROM / CD-RW / DVD-ROM (Option)
Expansion	2 x PCI
External I / O	
Front I / O	
USB 2.0	1 x USB Type A
Power Button	1
Rear I / O	
PS / 2 Keyboard	1
USB 2.0	4 x USB Type A
Powered Serial / COM	5 (COM1 / COM2 / COM3 / COM4 / COM5)
Serial RS485 / RS422	1 (COM6)
Cash Drawer	1 x RJ 11 (12V / 24V)
VGA	1 x DB 15F
Line-out	1
LAN (10 / 100)	1
Parallel	1 x DB 25F
DC 24V output	1
DC 12V output	1
Optional USB Box	
Powered USB (12V)	2
Powered USB (24V)	1
Powered USB (5V)	1
USB	4
Special feature	
Second HDD (hot swap)	Option
RAID	Built-in RAID 0,1
System ID	Built-in
Internal Header	
USB	4 (USB5 ~ 8)
Power button	1 (Pin Header)
Control / Indicator	
Power button	1 (Front)
LED Indicators	2 (HDD / Power)
Power	
Power Supply	230W
Environment	
EMC & Safety	FCC Class A / CE Marking / LVD
Operating Temperature	5°C ~ 35°C (41°F ~ 95°F)
Storage Temperature	-10°C ~ 60°C (14°F ~ 140°F)
Operating Humidity	20% - 85% RH non-condensing
Storage Humidity	5% - 90% RH non-condensing
Dimension (W x D x H)	270 x 300 x 120 mm (10.6" x 11.8" x 4.7")
Weight (kg / lbs)	N.W. 7 kgs / 15 lbs G.W. 8 kgs / 18 lbs
OS Support	Windows XP, WEPOS, XP Embedded, XP Professional for Embedded, Windows 2000 Professional Embedded, Linux

* USB 6 external port and internal header will be occupied, when USB HUB option is available

Product specification subject to change without prior notice.

©2007 Flytech Technology Co., Ltd. Registered trademarks and trademarks are property of their respective owners. The specification is subject to change without prior notice. Flytech endeavors to ensure that the information in this document is correct and fairly stated but does not accept liability for any error or omissions. The development of Flytech products and services is continuous, and published information may not be up to date. It is important to check the current position with Flytech.



FLYTECH Technology Co., Ltd.
No.168, Sing-ai Rd.,
Neihu District, Taipei City 114,
Taiwan
Tel: 886-2-8791-4988
Fax: 886-2-8791-4966
E-mail: sales@flytech.com.tw
www.flytech.com

USA
47825 Warm Springs boulevard., Fremont, CA 94539. Tel: 1-510-257-5180 Fax: 1-510-257-5181 Email: sales@flytech.com
Japan
2-48-14 Inada, Nagano-Shi, Nagano-Ken, Japan Post Zip Code: 381-0042 Tel: 81-26-259-4804 Email: flytech@flytech.co.jp
Hong Kong
Room 01, 6/F, Block A, Tonic Industrial Centre, 26 Kai Cheung Rd., Kowloon Bay, Kowloon, Hong Kong, China
Tel: 852-3525-5800 Fax: 852-2751-7447 Email: sales@flytech.com.hk
China
3F Building 39, No.333 Qin Jiang Rd., Shang-Hai 200233, China Tel: 86-21-5426-1555 Fax: 86-21-5426-1001 Email: sales@flytech.com.cn

S - 1008 - 0711 - P5000D