



POS790 Series

15"/17" Metal POS Terminal / Panel PC

POS 790 Series is a revolution All-in-One Metal Touch Screen POS Terminal or Digital Signage or Panel PC for the harsh retail or hospitality environment. Its ultra slim front bezel, water and grease resistant, exquisite stainless steel enclosure and rugged construction indeed are the best solution of any harsh environment. POS790 series is another powerful offering in restaurant, information kiosk, industrial automation, digital signage, commercial ads and healthcare. The sealed rugged housing is made by stainless steel and water & grease resistant for the harshest environment.



Metal Black POS Terminal



Stainless Steel POS Terminal

Features



1. Rugged metal housing and NEMA 4 / IP 65 dust & water proof display front.



4. Sealed rear cover and fanless/no air-vent design for the harshest environment
(for POS79xFL fanless models only)



2. 15", 17" display is 4:3



5. Slim HDD bay design for easy service and built-in speakers, and cable cover (option)
(for POS79x performance models only)



3. Rich I/O ports provides excellent peripheral connectivity



6. Ultra slim 30mm thickness stepping design; optional die-casting desktop stand

POS 790 Series

A powerful offering in digital signage, commercial ads, information kiosk, retail, hospitality, industrial automation and healthcare

Specification

Model Name	POS790		
Motherboard	B68	B98	C48
Processor	Intel® Atom™ N270 Processor 1.6GHz L2 512K FSB 533MHz	Intel® Celeron® M 1.86G / Core™ 2 Duo 1.66G / Core™ Duo 2.0G	Intel® Pineview D525 dual Core™ 1.8G L2 1M, FSB800MHz
Chipset	Intel® 945GSE Express + ICH7M	Intel® 945GME + ICH 7M FSB 533 / 667MHz	CPU with Graphic built-in + ICH 8M
System Memory	2 x DDR2 DIMM up to 2GB	2 x DDR2 DIMM socket up to 4GB FSB 533 / 667MHz	2 x DDR3 DIMM up to 4GB, FSB 800MHz
Graphic Memory	Intel® GMA 950 share system memory up to 224MB	Share system memory up to 244MB	Intel® GMA 3150 share system memory up to 256MB
LCD Touch Panel			
LCD Size	POS 795: 15" TFT LCD POS 797: 17" TFT LCD		
Brightness	POS 795: 250 cd/m ² POS 797: 300 cd/m ²		
Resolution	POS 795: 1024x768 POS 797: 1280x1024		
Touch Screen	Resistive		
Tilt Adjustment	0° ~ 90°		
Storage Device			
Hard Drive	1 x 2.5" SATA HDD bay		
Flash Memory	Compact Flash or SSD Solid State Drive or HDD (option)		
Expansion			
Mini PCI-E Slot	N/A	1	N/A
Mini PCI Slot	1	NA	1
Expansion I/O Ports			
USB Port	4 x USB 2.0		
PS/2	1		
Serial Port	4 x RJ45 COM (COM 3 / COM 4 pin 9 with 5V/12V)		
Parallel Port	1		
LAN Port	1 x RJ45 (10/100/1000Mbps Giga LAN)		
DC Jack	1		
Cash Drawer Port	1 x RJ11 (12V/24V cash drawer)		
MIC-in	1		
Line-out	1		
Power switch	1		
Power	Power Adapter (DC 90W, 19V, 4.7A)		
Peripheral			
Input Device			
MSR	MSR (PS/2)		
Output Device			
Customer Display	VFD display 2 x 20 characters (COM)		
Communication			
Wireless LAN	802.11 b/g/n wireless LAN card (option)		
Certificate			
EMC & Safety	FCC Class A / CE Mark / LVD		
Environment			
Operating Temperature	5°C ~ 35°C (41°F ~ 95°F)		
Storage Temperature	-20° ~ 55°C (-4°F ~ 131°F)		
Operating Humidity	20% - 80% RH non-condensing		
Storage Humidity	20% - 80% RH non-condensing		
Dimension (W x D x H)	POS795 LCD 90° tilt angle: 386 x 250 x 370 mm (15.2" x 9.8" x 14.6"), POS795 Wall mount: 386 x 60 x 308 mm (15.2" x 2.4" x 12.1") POS797 LCD 90° tilt angle: 411 x 250 x 390 mm (16.2" x 9.8" x 15.4"), POS797 Wall mount: 411 x 60 x 345 mm (16.2" x 2.4" x 13.6")		
Weight	POS795 (With metal stand): 9.5kg (20.9lbs) POS797 (With metal stand): 10.5kg (23.2lbs)		
OS Supported	Windows® XP, WEPOS, POSReady 2009, XP Embedded, XP professional for Embedded, Linux, Vista®, Windows® 7, WIN CE (for B68 & C48)		

Product specifications subject to change without prior notice.

©2010 Flytech Technology Co., Ltd. Registered trademarks and trademarks are property of their respective owners. The specification is subject to change without prior notice. Flytech endeavors to ensure that the information in this document is correct and fairly stated but does not accept liability for any error or omissions. The development of Flytech products and services is continuous, and published information may not be up to date. It is important to check the current position with Flytech.



FLYTECH Technology Co., Ltd.
No.168, Sing-ai Rd.,
Neihu District, Taipei City 114,
Taiwan
Tel: 886-2-8791-4988
Fax: 886-2-8791-4966
E-mail: sales@flytech.com.tw
www.flytech.com

U.S.A. - California
47825 Warm Springs Boulevard, Fremont, CA 94539, USA Tel: 1-510-257-5180 Fax: 1-510-257-5181 E-mail: sales@flytech.com
China - Shanghai
3F Building 39, No.333 Qin Jiang Rd., Shanghai 200233, P.R.China
Tel: 86-21-5426-1555 Fax: 86-21-5426-1001 http://www.flytech.com.cn E-mail: sales@flytech.com.cn
China - Hong Kong
Room 01, 6/F, Block A, Tonic Industrial Centre, 26 Kai Cheung Rd., Kowloon Bay, Kowloon, Hong Kong
Tel: 852-3525-5800 Fax: 852-2751-7447 http://www.flytech.com.hk E-mail: sales@flytech.com.hk
Japan - Nagano Ken
2-48-14 Inada, Nagano-Shi, Nagano-Ken, Japan Post Zip Code: 381-0042 Tel: 81-26-259-4804 E-mail: flytech@flytech.co.jp

1010 - P790b